

ASSEMBLY INSTURCTION

(FOR 6548)

Thank you for purchasing this quality product. Be sure to check all packing material carefully for small parts which may have come loose inside the carton during shipment.

- **Assemble the table on a flat, soft surface to prevent scratching the table finish. Read all instructions and study the drawings carefully before the assembly process.
- 1. Turn the pedestal upside down. Do not remove the plastic bolt protectors for this step.
- 2. Attach each foot to the pedestal as shown in the diagram by using washers and nuts supplied. Tighten all nuts firmly.
- 3. Turn the assembled pedestal right side up and place it in your desired location. Adjust the leg levellers at the bottom of each leg so that pedestal remains solid without rocking. Remove the plastic bolt protectors before doing the next step.
- 4. Release the brass sash locks located underneath the table.

 Then pull the ends of the table slightly apart and remove the center leaf of the tabletop.
- 5. Place the open table top over the pedestal and while aligning the holes in the table mounted boards with the bolts on the pedestal. Set the table down on the top of the pedestal.
- 6. Using washer & nuts supplied. Put on the washer and nut for each pedestal bolt as shown. Tighten the nut firmly with the wrench included.
- 7. Reinstall the leaf onto the tabletop. Close the table by pushing on the ends, and tighten the sash locks.

HARDWARE LIST:

a.	NUT	0)	5/16"	12PCS
h	FLAT WASHER	6	5/16"	12PCS

LOCK WASHER 🐧 5/16" 12 PCS

. WRENCH S 1 PC

e. LEVELER 4 PC





